

Dulux Professional Enviro2 Interior Low Sheen

PRODUCT CODE 560 LINE

Data Sheet No. AUDD1274

APPROVALS APAS 0215/3

Description

Dulux Professional Enviro2 Low Sheen Interior Acrylic is a premium, washable, scrubbable, hard wearing, new generation low VOC acrylic product that provides an elegant low sheen finish for interior walls in general living areas. The low VOC and low odour formulation contributes positively to indoor air quality and reduced air pollution.

Features

No solvents, water based
 Premium Acrylic paint
 Attractive low sheen finish
 Washable

Benefits

Low odour, no aggravating fumes, same day recoat
 Provides hardwearing properties and suitability for 'wet' areas
 Aesthetic appeal of low gloss level suitable for walls
 Marks and soiling can be easily removed

Uses

Dulux Professional Enviro2 Low Sheen Interior Acrylic is a washable low sheen for use on all interior walls and is particularly recommended for heavy traffic wall areas in family rooms, children's rooms, hallways and other areas where fumes can be a problem and a washable finish is required.

Performance Guide

Weather	Designed for interior use only. Not recommended for exterior use.	Heat	Softens and sticks to other painted surfaces over 70°C
Water	Suitable for use in wet areas	Solvent	Sensitive to aromatic hydrocarbons and alcohols
Abrasion	Good wet and dry burnish resistance		

Typical Properties and Application Data

Gloss Level	5-10 at 60 degrees, 5-15 at 85 degrees	Thinner	Water
Gloss Level Ind		Spread Rate	16.0 sqm/L
Volume Solids	35.0	Components	1
Colour	White, Deep, Ultra Deep, Extra Bright	Toxicity	Lead Free. Dry film is non-toxic and conforms to AS1647, Part 3.
Number of Coats	2	V.O.C Level	<1 g/L untinted
Wet film per coat	Recommended 63 µm	Touch Dry	30 Minutes
Dry film per coat	Recommended 25 µm	Clean Up	Clean all equipment with water
Recoat	2 Hours		


Application Method


Dulux Professional Enviro2 Interior Low Sheen

Data Sheet No.	AUDD1274
----------------	----------

Application Guide

Surface Preparation

All surfaces must be prepared in accordance with proper trade practices and must be clean and free from dust, dirt, grease and oil. previously painted surfaces, except asbestos cement, must be sanded to remove loose, peeling, flaking or chalky paint. Spot prime bare areas.

Note: To avoid dust from asbestos cement sheeting do not sand or scrub. Wash with bleach solution or appropriate de-mossing chemical where necessary. Wash down.

Application Procedure and Equipment

Stir well before use with a broad, flat paddle using an up and down scooping action. Apply 2 coats of Dulux Professional Enviro2 Interior Low Sheen. Thin with up to 100ml of water per litre if necessary.

Brush, roller, spray

Health and Safety

MSDS Number 20968

Health Effects For detailed information refer to the product label and the current Material Safety Data Sheet available by calling Dulux Australia Toll free phone 13 23 77. Health effects: Splashes to the eye may cause eye irritation.

Protective Equipment Personal Protective Equipment: Wear eye protection.

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not use at temperatures below 10°C, or when the temperature of surface may fall below 10°C during the drying period. Not recommended for application at temperatures higher than 28°C. Avoid exposure to steam and condensation for 48 hours after application. Although the film is touch dry in 30 minutes allow 7 days for film to fully cure before washing.

Cleaning schedule: After application, allow the surface to dry for 7 days prior to cleaning. Do not scrub the surface, use abrasive cleaners or solvent. The surface should be wiped down with a soft damp cloth using mild detergent such as Spray & Wipe or similar.

Transport and Storage

Pack A 560 LINE

Sizes 4 Litre 10 Litre 15 Litre

Weight 5.6 Kg 13.9 Kg 21.3 Kg

Dangerous Goods Class NA

Shipment Name Not dangerous goods. No special transport requirements.

Flash point NA

UN Number NA

Package Group NA

Data Sheet	Dulux Professional Enviro2 Interior Low Sheen		
DuSpec Data Code	AUDD1274	Page No	2 of 3
Issue No	13.0	Date Issued	21/06/2010



DATA SHEET



Dulux Professional EnvirO2 Interior Low Sheen	
	Data Sheet No. AUDD1274

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Dulux Professional EnvirO2 Interior Low Sheen		
DuSpec Data Code	AUDD1274	Page No	3 of 3
Issue No	13.0	Date Issued	21/06/2010