



PRIMECOTE SEALER PRIMER

Data Sheet

DESCRIPTION

Primecote Sealer Primer is a water based 100% acrylic sealer primer supplied as a milky white substance. When dried the solution appearance becomes a clear film.

FEATURES + BENEFITS

Water Based	Easy application and easy clean up.
Good Adhesion	Ensures the durability of Elastacote Membrane
Fast Dry	Recoat after 2 hours.

USES

The Primecote Sealer Primer has been designed to seal and prime surfaces and enhance the adhesion of the Elastacote Membrane. Correct application ensures maximum coverage of the Membrane coating.

PERFORMANCE GUIDE

Weather	N/A	Solvent	N/A	Salt	N/A	Abrasion	N/A
Heat	N/A	Acid	N/A	Water	N/A	Alkali	N/A

TYPICAL PROPERTIES

Gloss Level	Medium	Clean up	Water
Gloss Level Ind	5 10 20 30 40 50 60 70 80 90 100	Thinner	Not recommended
Volume Solids (%)	30.6	Spread Rate	8 - 10 sqm/L
Mass Solids (%)	31.3	Components	1
Colour	Clear	Toxicit	Lead free. Dry film is non-toxic
Number of Coats	1 minimum	Shelf life	24 months maximum
V.O.C	Level < 20 g/L untinted	Wet film per coat	Recommended 100 µm
Touch Dry Recoat	30 minutes	Dry film per coat	Recommended 30 µm
Recoat	2 hours	Size	20 litres

APPLICATION PROCESS

Refer to finishing coat data sheet.

HEALTH + SAFETY

MSDS: Available on request. Please visit the Globalcote Website - www.globalcote.com.au.

RECOMMENDATIONS + PRECAUTIONS

- Always use and store this product in a well ventilated area
- Ensure that the surface is sound, clean and dry
- Wear appropriate safety clothing, shoes, glasses and gloves at all times
- In the case of emergency please call 000
- Do not apply where rain is imminent. High humidity may effect curing times. Weather conditions must be considered and deemed suitable before proceeding with application of the Globalcote system
- Ensure that the application of the Primecote Sealer Primer is in accordance to the Globalcote recommendations
- Due care and consideration should be taken where water collection methods are present. Globalcote recommend allowing our system 7 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.
- Ensure that workplace health and safety methods are used when working with this product
- Dangerous Goods Class = Not Applicable - Not considered dangerous for transportation of this product

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Globalcote product are beyond Globalcote's control. Globalcote recommends that the applicator of this product determines the suitability of the Globalcote material and its recommendations prior to use or application.